

Robot Equipment Automotive


Robotube

RACCORDI PER ROBOTUBE


Raccordi femmina a ghiera (ottone / acciaio inox)

	Articolo	Ø mm	Pollici	Filettatura metallica	Ghiera esagonale
	2.308.937	6	1/4	M14 x 1,5	17
2.308.938	9	3/8	M16 x 1,5	19	
2.408.938	9	3/8	M22 x 1,5	27	
2.308.939	12	1/2	M22 x 1,5	27	
2.188.941	19	3/4	M30 x 2	36	
2.308.942	25	1	M36 x 2	41	


Raccordi femmina a ghiera con angolo di -45°

	Articolo	Ø mm	Pollici	Filettatura metallica	Ghiera esagonale
	2.308.937/45	6	1/4	M14 x 1,5	17
2.308.938/45	9	3/8	M16 x 1,5	19	
2.308.939/45	12	1/2	M22 x 1,5	27	


Raccordi femmina a ghiera con angolo di -90°

	Articolo	Ø mm	Pollici	Filettatura metallica	Ghiera esagonale
	2.308.937/45	6	1/4	M14 x 1,5	17
2.308.938/45	9	3/8	M16 x 1,5	19	
2.308.939/45	12	1/2	M22 x 1,5	27	


Raccordo Bifacciale

	Articolo	Pollici	
	2.227.346	1/4	
	2.227.347	3/8	
	2.227.348	1/2	
	2.227.349	3/4	


Raccordo Maschio G/M

	Articolo		Filettatura
	2.141.413		G1/4—M14 x 1,5
	2.381.613		G3/8—M16 x 1,5
	2.122.213		G1/2—M22 x 1,5

Raccordo Maschio Vite Doppia

	Articolo		Filettatura
	2.241.414		M14 x 1,5
	2.252.222		M22 x 1,5

Raccordo Maschio Grande

	Articolo		Filettatura
	2.221.616		M16 x 1,5
	2.222.222		M22 x 1,5

Raccordo Maschio Grande con Uscita M14 x 1,5

	Articolo		Filettatura
	2.242.222		M22 x 1,5