



APPLIANCE WIRING MATERIAL

Subj.758

Section 3

Page 3266

Issued:1972-05-30

Revised:2011-08-16

Style 3266

Single conductor with extruded insulation

Rating	125 deg C, 300 Vac, Horizontal flame.
Conductor	32 AWG - 10 AWG, solid or stranded.
Insulation	Extruded XLPE, 15 mils min average, 13 mils minimum at any point.
Standard	Appliance Wiring Material UL 758.
Marking	General.
Use	Internal Wiring. Tags may indicate the following: 600 Volts Peak - For Electronic Use Only.

UL and the UL Logo are trademarks of UL LLC © 2018

Consigliato da:



SEVI KABEL

VIA DEI MARINAI D'ITALIA, 1 - 10034 CHIVASSO (TO) - Tel. 011.910.11.12 / 011.910.67.78 - Fax 011.913.13.13 - info@sevikabel.it



APPLIANCE WIRING MATERIAL

Subj.758

Section 3

Page 3173

Issued:1962-07-10

Revised:2013-11-22

Style 3173

Single Conductor with Extruded Insulation

Rating	125 deg C, 600 Vac, Horizontal flame.
Conductor	26 AWG - 9 AWG, solid or stranded.
Insulation	Extruded XLPE, 30 mils minimum average thickness, 27 mils minimum thickness at any point.
Standard	Appliance Wiring Material UL 758.
Marking	General.
Use	Internal wiring of appliances.

UL and the UL Logo are trademarks of UL LLC © 2018

Consigliato da:



SEVI KABEL

VIA DEI MARINAI D'ITALIA, 1 - 10034 CHIVASSO (TO) - Tel. 011.910.11.12 / 011.910.67.78 - Fax 011.913.13.13 - info@sevikabel.it



APPLIANCE WIRING MATERIAL

Subj.758 Section 3 Page 3271

Issued:1972-08-02

Revised:2015-08-13

Style 3271 Single conductor with extruded insulation

Rating 125 deg C, 600 Vac, 750 Vdc, Horizontal flame.

Semi-Conductive Layer Optional, extruded or non-extruded semi-conductive polymeric layer may be provided over the conductor.

Conductor 30 AWG - 2000 kcmil, solid or stranded.

Insulation Extruded XLPE.

<u>Conductor size</u>	<u>Minimum average thickness</u>	<u>Minimum thickness at any point</u>
30-9 AWG	30 mils	27 mils
8-2 AWG	45 mils	40 mils
1-4/0 AWG	55 mils	50 mils
213-500 kcmil	65 mils	58 mils
501-1000 kcmil	80 mils	72 mils
1001-2000 kcmil	95 mils	86 mils

Standard Appliance Wiring Material UL 758.

Marking General.

Use For use as Motor Leads or Internal Wiring of appliances. Tags may indicate the following: 2500 volt peak - For Electronic Use Only.

UL and the UL Logo are trademarks of UL LLC © 2018

Consigliato da:



SEVI KABEL

VIA DEI MARINAI D'ITALIA, 1 - 10034 CHIVASSO (TO) - Tel. 011.910.11.12 / 011.910.67.78 - Fax 011.913.13.13 - info@sevikabel.it