



APPLIANCE WIRING MATERIAL

Subj.758

Section 3

Page 3239

Issued:1969-10-13

Revised:2014-08-06

Style 3239

High voltage DC wire with extruded or non-extruded insulation

**Rating**

Maximum 200 deg C, 60000 Vdc, Horizontal flame and VW-1 flame. See facing page for temperature and voltage ratings.

**Conductor**

24-10 AWG copper or nickel, or 12-10 AWG aluminum, or 27-20 AWG Resistance Wire; solid or stranded. Or 24-10 AWG solid or stranded coated high strength copper - min 90% conductivity. Aluminum conductors shall be permitted for a 90 deg C maximum operating temperature. Copper conductors may be tinned, silver or nickel plated, heat bonded or overcoated.

**Insulation**

Extruded or non-extruded Thermoplastic and/or Thermosetting. See facing page for details.

**Shield**

Optional. See facing page for details.

**Covering**

Optional. See facing page for details.

**Jacket**

Optional. See facing page for details.

**Standard**

Appliance Wiring Material UL 758.

**Use**

Internal wiring of TV receivers or where the acceptability has been determined by Underwriters Laboratories.

UL and the UL Logo are trademarks of UL LLC © 2018

Consigliato da:



**SEVI KABEL**

VIA DEI MARINAI D'ITALIA, 1 - 10034 CHIVASSO (TO) - Tel. 011.910.11.12 / 011.910.67.78 - Fax 011.913.13.13 - info@sevikabel.it