



APPLIANCE WIRING MATERIAL

Subj.758            Section 3            Page 3068

Issued:1959-05-01

Revised:2014-07-02

Style 3068            Single conductor with extruded insulation and  
other-than-extruded covering

**Rating**            150 deg C, 300 Vac, Horizontal flame.

**Conductor**        30 AWG - 16 AWG, solid or stranded.

**Insulation**        Extruded SR, 15 mils minimum average thickness,  
13 mils minimum thickness at any point.

**Covering**         Same as for Type SF-1 Fixture Wire.

**Standard**         Appliance Wiring Material UL 758.

**Marking**          General.

**Use**                Internal Wiring.

UL and the UL Logo are trademarks of UL LLC © 2018

Consigliato da:



**SEVI KABEL**

VIA DEI MARINAI D'ITALIA, 1 - 10034 CHIVASSO (TO) - Tel. 011.910.11.12 / 011.910.67.78 - Fax 011.913.13.13 - info@sevikabel.it



APPLIANCE WIRING MATERIAL

Subj.758            Section 3            Page 3132

Issued:1960-12-19

Revised:2014-03-14

Style 3132            Single conductor with extruded insulation

- Rating**                    150 deg C, 300 Vac, Horizontal flame.
- Conductor**                30 AWG - 4/0 AWG, solid or stranded.
- Insulation**                Extruded SR, 15 mils minimum average thickness,  
13 mils minimum thickness at any point.
- Covering**                    Optional. Same as SF-1.
- Standard**                    Appliance Wiring Material UL 758.
- Marking**                    General.
- Use**                            Internal wiring where totally enclosed.

UL and the UL Logo are trademarks of UL LLC © 2018

Consigliato da:



**SEVI KABEL**

VIA DEI MARINAI D'ITALIA, 1 - 10034 CHIVASSO (TO) - Tel. 011.910.11.12 / 011.910.67.78 - Fax 011.913.13.13 - info@sevikabel.it



APPLIANCE WIRING MATERIAL

Subj.758            Section 3            Page 3069

Issued:1959-05-01

Revised:2014-07-02

Style 3069            Single conductor with insulation and other-than-extruded covering

**Rating**                    150 deg C, 600 Vac, Horizontal flame.

**Conductor**                26 AWG - 20 AWG, solid or stranded.

**Insulation**                Extruded SR, 30 mils minimum average thickness, 27 mils minimum thickness at any point.

**Covering**                 Same as for Type SF-2 Fixture Wire.

**Standard**                 Appliance Wiring Material UL 758.

**Marking**                 General.

**Use**                        Internal wiring.

UL and the UL Logo are trademarks of UL LLC © 2018

Consigliato da:



**SEVI KABEL**

VIA DEI MARINAI D'ITALIA, 1 - 10034 CHIVASSO (TO) - Tel. 011.910.11.12 / 011.910.67.78 - Fax 011.913.13.13 - info@sevikabel.it



APPLIANCE WIRING MATERIAL

Subj.758            Section 3            Page 3070

Issued:1959-05-01

Revised:2012-04-10

Style 3070            Single conductor wire using other-than-extruded covering.

- Rating**                    150 deg C, 600 Vac, Horizontal flame.
- Conductor**                18 AWG - 12 AWG, solid or stranded.
- Insulation**                Extruded SR, 30 mils minimum average thickness, 27 mils minimum thickness at any point.
- Covering**                    Same as for Type SFF-2 Fixture Wire.
- Standard**                    Appliance Wiring Material UL 758.
- Marking**                    General.
- Use**                            Internal wiring.

UL and the UL Logo are trademarks of UL LLC © 2018

Consigliato da:



**SEVI KABEL**

VIA DEI MARINAI D'ITALIA, 1 - 10034 CHIVASSO (TO) - Tel. 011.910.11.12 / 011.910.67.78 - Fax 011.913.13.13 - info@sevikabel.it



APPLIANCE WIRING MATERIAL

Subj.758            Section 3            Page 3535

Issued:1990-02-16

Revised:2015-10-13

Style 3535            Single conductor with insulation and covering.

**Rating**                    150 deg C, 600 Vac, Horizontal flame.

**Conductor**                20 AWG - 500 kcmils, solid or stranded copper.

**Separator**                Optional.

**Insulation**                Extruded Silicone rubber.

<u>Conductor size(AWG).</u>	<u>Minimum average thickness(mils).</u>	<u>Minimum thickness at any point(mils).</u>
20 - 12	30	27
11 - 8	45	40
7 - 2	60	54
1 - 3/0	80	76
4/0 - 500	95	85

**Covering**                    Same as for Type SFF Fixture Wire.

**Standard**                    Appliance Wiring Material UL 758.

**Marking**                    General.

**Use**                            Internal Wiring of Appliances.

UL and the UL Logo are trademarks of UL LLC © 2018

Consigliato da:



**SEVI KABEL**

VIA DEI MARINAI D'ITALIA, 1 - 10034 CHIVASSO (TO) - Tel. 011.910.11.12 / 011.910.67.78 - Fax 011.913.13.13 - info@sevikabel.it